

92751

## ShieldECO CCT

### FEATURES

- 3 years (2 years + 1 year) extended warranty
- Matt white & clear acrylic finish (white bezel included)
- Constructed from steel & acrylic
- Fire rated to 60 & 90 minutes
- Tested with insulation cover thickness 300mm
- Suitable for bathroom zone 2
- Suitable for bathroom zone 1 if used in conjunction with a 30MA RCD
- IP65

### SPEC DATA

Product Wattage:	5W
Product Lumen:	500
Lumen/W:	100
Kelvin:	3000/4000/6000K
SDCM:	6
CRI:	80
Dimmable:	Yes
Lifetime (Hours):	30000
Beam Angle:	60°
Power Factor:	0.9
Driver Type:	Constant Current 90mA
Inrush Current at Start Up:	Max. 20A
Energy Rating:	D
Product Voltage:	220-240V
Hertz:	50/60
Surge Protection (KV):	2
Operating Temp.:	-20 to 40 Degree
Product Weight (KG):	0.134
Cut-out (mm):	Ø64mm
Minimum Cavity Depth (mm):	63mm
Terminal Block:	3 way quick fit
Class:	2

### ACCESSORIES

- 95202, ShieldECO satin bezel
- 95203, ShieldECO chrome bezel
- 95204, ShieldECO black bezel
- 101345, Dimmer module 100W universal
- 101346, Dimmer module 250W trailing edge
- 103944, EM conversion kit 8W

