OUTDOOR DECORATIVE WALL LIGHT PATHLUX BRICK IP65 150LM 3W 3000K DOWN LIGHT DARK GREY

BLA017



Light up the exterior of your home with these compact, stylish an contemporary LED luminaires. Weatherproof and hard-wearing, this range is designed to last against the elements while bringing a designer look to your surroundings. Gently illuminate your pathways with the stylish and hardwearing Pathlux. This model features a Brick design in dark grey.

Details

| Barcode: Category: Range Name: | 5055788232827 Luminaires Wall Light |
|--------------------------------------|---|
| Product Type: | Outdoor |
| Market Segment: Warranty | Residential Outdoor |
| (Years): | 3 |
| CE RoHS: | Yes |
| Physical Data | |
| Product Length (mm): | 210 |
| Product Depth (mm): | 30 |
| Product Width (mm): | 85 |
| Product Weight (g): Optic: | 226 |
| Material: | Clear Polycarbonate diffuser |
| Luminaire Fixing: | Polycarbonate body |
| Placement / Application: | Wall Mounted |
| | Outdoor, General Lighting |
| Electrical Data | |
| Power Consumption (W) : | |
| Power Factor: | 3 |
| Voltage Range (v): | 0.3 |
| Dimming: | |
| Driver Included: | 220-240 |
| Electric Current: | Non-Dimmable |
| EN: | Yes |
| | AC |
| | EN-60598 |
| | |

LVD Certified:

Light Data

| Luminous Flux in Lumens (Im): | 150 |
|--|------------------------------|
| Luminous efficacy (Im/W): | 50 |
| Correlated Colour Temperature (CCT) (K): | 3000 |
| Colour Temperature: | 3000 |
| Colour Temperature Name: | Warm White |
| Colour Rendering Index (CRI): | 80 |
| Frequency Range (Hz): | 50/60 |
| Instant on (Less than 1 second): | Yes |
| LED Type: | Surface mounted device (SMD) |
| Lifetime (hours): | 25000 |
| Switching Cycles: | 12500 |

Environment

| EN: | EN-60598 |
|-------------------------------------|----------|
| LVD Certified: | Yes |
| CE RoHS: | Yes |
| New Energy Rating: | G |
| EU Luminaire: | L |
| Hg 0% (Mercury Free): | Yes |
| IP Rating (Ingress Protection): | IP65 |
| Lowest Operating Temperature (°C): | -20 |
| Maximum Operating Temperature (°C): | 60 |

Packaging

| Package Length (mm): | 215 |
|----------------------|-----|
| Package Width (mm): | 40 |
| Package Depth (mm): | 100 |