

SPEY TILT.

The SPRY Fire Rated Downlight, with an IP65 rating, is fully adjustable ideal for diverse environments such as bathrooms, kitchens, soffits, offices, and living areas. Suitable for both domestic and commercial use



- ✓ Switchable Color: 2700K, 3000K, 4000K, 6000K
- ✓ High Luminosity: Delivers 525-580 Lumens
- ✓ Fire Rated: Certified for 30, 60, and 90 Minutes
- ✓ Fully Dimmable: Smooth Flicker-Free Dimming 0-100%
- ✓ Engineered Joist Tested: I-Joist & Posi Joist
- ✓ Insulation Coverable



Technical Specification

Product Details

Range Variants	Standard
Trim Options	White
Applications	Semi-Commercial or Residential
Installation Options	Ceilings / Bathrooms / Showers / Soffits
UKCA & CE Compliant	Yes
RoHS Compliant	Yes
Warranty Period	5 year

Construction

Case Material	Pressed Steel
Case Colour	Blue
Lens Material	Glass
Lens Colour	Opaque
Trim Colour Options	White / Brushed Chrome / Polished Chrome
IP Rating	IP65
Bathroom Zone	Zones 1 & 2
Dimensions	Diameter: 75mm Depth: 30mm
Cut-Out	Diameter: 60mm
Weight	TBC
Cable Entry	Loop-in / Loop-out driver
Operating Temp	-20 to 45 °C

Electrical Data

Voltage	220-240V AC
Frequency	50/60Hz
Wattage	5.0W
Amperage (mA)	TBC
Power Factor	TBC
Earth Protection	Class I
Energy Rating	E
Dimmable	0-100% Dimmable

Lamp Data

LED Type	SMD
LED Microchip	2835
Lumens	525-580 lm
Lumens per Watt	116.0 lm/w
Colour Rendering Index	>=80 CRI
Colour Temperature	CCT Switchable 2700K, 3000K, 4000K & 6000K
Beam Angle	60°
Instantaneous Illumination	Yes: <1 second
LED Lifetime	50,000 hrs

Product Family

FRCCT5AD White

